## U.S. DÉPARTMENT OF HOMELAND SECURITY Federal Emergency Management Agency National Flood Insurance Program

EMB No. 1660-0008 Expraint Date November 30, 2022

# **ELEVATION CERTIFICATE**

Important: Follow the instructions on pages 1-9.

NOV 04 2021

Copy all pages of this	Elevation Co	ertificate and all attach	ments fo	r (1) commur	nity official (2) ins	urance	agent/company and (3) building	AMue
Copy all pages of this Elevation Certificate and all attachments for (1) community official (2) insurance agent/c BOROL SECTION A - PROPERTY INFORMATION					FOR INSURANCE COMPAE			
A1. Building Owner's Name Policy Numl						Policy Number:	MARKEN CO.	
Daniel S. & Loretta				***				
A2. Building Street Address (including Apt., Unit, Suite, and/or Bldg. No.) or P.O. Route and Company I 254 88th Street						Company NAIC Number:		
City	The same of the sa	The state of the s	VP-4-14007 RL 1-01400-0	State			ZIP Code	alatitiner salamanner
Stone Harbor	Tiew delecy delect						08247	
A3. Property Desc Block 87.03 Lots		and Block Numbers, T	ax Parce	l Number, Le	gal Description,	etc.)		
A4. Building Use	(e.g., Reside	ntial, Non-Residential,	Addition	, Accessory,	etc.) Resider	ntial		
A5. Latitude/Long	itude: Lat. <u>N</u>	N 39°03'33.50"	Long. V	V 074°45'19.	30" Horizon	tal Dati	ım: NAD 1927 X NAD 19	383
A6. Attach at leas	t 2 photograp	phs of the building if th	ne Certific	cate is being	used to obtain flo	ood insu	rance.	
A7. Building Diagr								
A8. For a building	with a crawls	space or enclosure(s).						
		Ispace or enclosure(s)			1367.00 sq ft			
b) Number of	permanent fi	ood openings in the cr	rawlsnac			ot abou	e adjacent grade 7	
		penings in A8.b				OL BDOV	e adjacent grade /	
				1400.00 Sq II				
d) Engineere	i tioog openii	ngs? ⊠ Yes 🔲 I	No					
A9. For a building	with an attacl	hed garage:						
a) Square foot	age of attacl	hed garage		N/A sq f	t			
b) Number of	permanent fle	ood openings in the at	tached g	arage within	1.0 foot above a	diacent	grade N/A	
				N/A so			Section of the sectio	
				10/11 30	· · · ·			
a) Engineered	nooo openir	ngs? Yes 🗓 Yes	NO					
AND A WORLD AND AND AND AND AND AND AND AND AND AN	SE	ECTION B - FLOOD	INSURA	NCE RATE	MAP (FIRM) IN	FORM	ATION	f 27-24 107-000m
B1. NFIP Commun	THE PROPERTY OF STREET AND ASSESSED.	Community Number		B2. County	THE RESERVE TO THE PERSON NAMED IN COLUMN 2 ASSESSMENT OF THE PERSON		B3. State	Militario in company
Borough of Stone I				Cape May			New Jersey	
B4. Map/Panel Number	B5. Suffix	B6. FIRM Index Date	Effe	Effective/   Zone(s)   (Zone		Base Flood Elevation(s) (Zone AO, use Base Flood Depl	 (h)	
34009C242	F	10-05-2017	10-05-2	vised Date 2017	AE .	8		
		Base Flood Elevation Community Deter				d in Ite	m B9:	
B11. Indicate eleva	ation datum u	used for BFE in Item B	9: 🗀 N	GVD 1929	⊠ NAVD 1988		ther/Source:	
B12. Is the building	located in a	Coastal Barrier Reso	urces Su	etem (CRPS	area or Otheru	ico Droi	ected Area (OPA)?  Yes 🔀	
Designation I		-			, area or Otherw	136 110	ected Area (OPA)? Yes X	No
Designation t	Jale.		CBRS	☐ OPA				

# ELEVATION CERTIFICATE

OMB No. 1660-0008 Expiration Date: November 30, 2022

	py the corresponding information	TOUR BUTCH THE PROPERTY OF THE	FOR INS	JRANC	CE COMPANY U	
254 88th Street	Apt., Unit, Suite, and/or Bldg. No.) or		Policy Nu			
City Stone Harbor	State ZIP Code Harbor New Jersey 08247			Company NAIC Number		
SECTIO	ON C BUILDING ELEVATION IN	FORMATION (SURVEY	REQUIRED)	MONTH AND POST OF BEIN	eneckierostanierostas vo trypykosi	
	will be required when construction of			-		
C2. Elevations – Zones A1–A30, Complete Items C2.a–h belo Benchmark Utilized: PID# DI	AE, AH, A (with BFE), VE, V1–V30, w according to the building diagram (P1519 Vertical Vertica	V (with BFE), AR, AR/A, A specified in Item A7. In Pu al Datum: <u>NAVD 1988</u>	R/AE, AR/A1 erto Rico only	-A30, / , enter	AR/AH, AR/AO. meters.	
	d for the elevations in items a) through IAVD 1988 [] Other/Source:	gh h) below.				
Datum used for building elevi	ations must be the same as that used	d for the BFE.	Check	the me	easurement used	
a) Top of bottom floor (include	ding basement, crawlspace, or enclose	sure floor)		feet	meters	
b) Top of the next higher flo			11:3	feet	meters	
c) Bottom of the lowest horiz	ontal structural member (V Zones or	nly)	N/A X	feet	meters	
	d) Attached garage (top of slab)				meters	
<ul> <li>e) Lowest elevation of mach (Describe type of equipment)</li> </ul>	inery or equipment servicing the build ent and location in Comments)	ding	11.3 ×	feet	meters	
f) Lowest adjacent (finished	f) Lowest adjacent (finished) grade next to building (LAG)			feet	meters	
g) Highest adjacent (finished	d) grade next to building (HAG)	AND THE STATE OF T	5.4 ×	feet	meters	
<ul> <li>h) Lowest adjacent grade at structural support</li> </ul>	lowest elevation of deck or stairs, inc	cluding	5.3 🔯	feet	meters	
SECT	ON D SURVEYOR, ENGINEER,	OR ARCHITECT CERT	FICATION		AFT OF THE PROPERTY OF A P. P.	
I certify that the information on thi statement may be punishable by i	nd sealed by a land surveyor, engine s Certificate represents my best effor fine or imprisonment under 18 U.S. C	rts to interpret the data ava Code, Section 1001.	ilable. I unde	rstand t	hat any false	
The second secon	ction A provided by a licensed land s	urveyor? La Yes La No	≥ Che	ck here	e if attachments.	
Certifier's Name Steven C. Woodrow	License Nui 27514	mber			A TO COMPANY OF THE PARTY OF TH	
Title	F101.4					
Professional Land Surveyor				PI	aice	
Company Name Dante Guzzi engineering Associal	tes			6	eal	
Address 118 Stokes Road	Service de la company de la co			1-1	G) G	
City Medford	State New Jersey	ZIP Code 08055				
Signature Star ( (	Date 11-01-2021	Telephone (609) 654-4440	Ext.	P407000 A.F4000000 M.VII	An Philippical St. VI Kingson Philippical Analysis	
Copy all pages of this Elevation Cer	tificate and all attachments for (1) com	nmunity official, (2) insurance	e agenVcomp	any, and	d (3) building owi	
he lowest equipment visible at th	oment and location, per C2(e), if appl e time of the Survey was the HVAC to certified to provide 200 SF of flood p	unit located outside the bui	lding. The fou	indation	n vents are	
Proj# M2100192.01						
		WHO WESTERS STATES AND A TOWN CORPOR HEAD A WOOD CONTROL OF THE STATES AND A STATE OF THE STATES AND A STATE OF THE STATES AND A STATE OF THE STATE				

# **ELEVATION CERTIFICATE**

OMB No. 1660-0008 Expiration Date: November 30, 2022

IMPORTANT: In these spaces, copy the correspond	ling information	from Section	on A.	FOR INSURA	NCE COMPANY USE
Building Street Address (including Apt., Unit, Suite, an 254 88th Street	g Street Address (including Apt., Unit, Suite, and/or Bldg. No.) or P.O. Route and Box No. th Street			Policy Numbe	
City Stone Harbor	State New Jersey	ZIP Co 08247		Company NAI	C Number
SECTION E – BUILDING EL FOR ZON	EVATION INFO	RMATION E A (WITH	(SURVEY NOT OUT BFE)	REQUIRED)	t aut 8 des jazon es filosopo para per cur que es estantida háci abbestar abs e volunt es
For Zones AO and A (without BFE), complete Items E complete Sections A, B,and C. For Items E1–E4, use enter meters.  E1. Provide elevation information for the following and the highest adjacent grade (HAG) and the lowest a) Top of bottom floor (including basement, crawlspace, or enclosure) is  b) Top of bottom floor (including basement, crawlspace, or enclosure) is  E2. For Building Diagrams 6–9 with permanent flood of the next higher floor (elevation C2.b in the diagrams) of the building is  E3. Attached garage (top of slab) is  E4. Top of platform of machinery and/or equipment servicing the building is  E5. Zone AO only: If no flood depth number is availab floodplain management ordinance?	natural grade, if a d check the appro adjacent grade (L  ppenings provided	vailable. Ch priate boxes AG).  In Section  In Section In Section Ilo	eck the measure s to show whethe feet mete feet mete A Items 8 and/or feet mete feet mete feet mete feet mete feet meter	ment used. In P or the elevation i or above o	uerto Rico only, s above or below  r
SECTION F - PROPERTY OW	TIANA MA PERMITANA MANAGEMENTA AND AND AND AND AND AND AND AND AND AN				TATION IN SECTION G.
The property owner or owner's authorized representati community-issued BFE) or Zone AO must sign here. T	CHARLES ON A STREET WAS THE STREET, THE ST	THE RESIDENCE WHEN THE STATE	NAME AND ADDRESS OF THE POST OFFICE AND ADDRESS OF THE POST OF THE	MARKANDERS OF THE PARTY OF THE	FEMA-issued or
Property Owner or Owner's Authorized Representative		Sections A,	B, and E are cor	rect to the best	of my knowledge.
	s Name				
Address	(	City	Sta	ate	ZIP Code
Signature		ate	Te	lephone	
Comments					
				Check h	ere if attachments.

# ELEVATION CERTIFICATE

OMB No. 1660-0008 Expiration Date: November 30, 2022

IMPORTANT: In these spaces, copy the corresponding information from Section A.	FOR INSURANCE COMPANY USE
Building Street Address (including Apt., Unit, Suite, and/or Bldg No.) or P.O. Route and Box No. 254 88th Street	Policy Number:
City State ZIP Code Stone Harbor New Jersey 08247	Company NAIC Number
SECTION G - COMMUNITY INFORMATION (OPTION	AL)
The local official who is authorized by law or ordinance to administer the community's floodplain Sections A, B, C (or E), and G of this Elevation Certificate. Complete the applicable item(s) and used in Items G8–G10. In Puerto Rico only, enter meters.  G1. The information in Section C was taken from other documentation that has been sign engineer, or architect who is authorized by law to certify elevation information (Indica data in the Comments area below.)  G2. A community official completed Section E for a building located in Zone A (without a or Zone AO.  G3. The following information (Items G4–G10) is provided for community floodplain mana G4. Permit Number G5. Date Permit Issued G7. This permit has been issued for:  [G4. Permit Number G5. Date Permit Issued G7. This permit has been issued for:  [G6. Date Permit Issued G8. Elevation of as-built lowest floor (including basement) G7. The building:  [G7. This permit has been issued for:  [G8. Elevation of as-built lowest floor (including basement) G7. The building:  [G9. BFE or (in Zone AO) depth of flooding at the building site:  [G8. Elevation of Substantial Improvement G8. Elevation of Substantial Improvement G9. Elevation G8. Elevation of Substantial Improvement G9. Elevation G8. Elevation of Substantial Improvement G9. Elevation G8. Elevat	management ordinance can complete sign below. Check the measurement dealed by a licensed surveyor, the the source and date of the elevation of the source of the sourc
	☐ Check here if attachments.



# ICC-ES Evaluation Report

ESR-2074

Reissued February 2021

This report is subject to renewal February 2023.

www.icc-es.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

DIVISION: 08 00 00—OPENINGS Section: 08 95 43—Vents/Foundation Flood Vents

REPORT HOLDER:

SMART VENT PRODUCTS, INC.

#### **EVALUATION SUBJECT:**

SMART VENT® AUTOMATIC FOUNDATION FLOOD VENTS: MODELS #1540-520; #1540-521; #1540-510; #1540-511; #1540-570; #1540-574; #1540-524; #1540-514 FLOOD VENT SEALING KIT #1540-526

#### 1.0 EVALUATION SCOPE

Compliance with the following codes:

- 2018, 2015, 2012, 2009 and 2006 International Building Code® (IBC)
- 2018, 2015, 2012, 2009 and 2006 International Residential Code® (IRC)
- 2018 International Energy Conservation Code® (IECC)
- 2013 Abu Dhabi International Building Code (ADIBC)†

The ADIBC is based on the 2009 IBC 2009 IBC code sections referenced in this report are the same sections in the ADIBC.

#### Properties evaluated:

- Physical operation
- Water flow

### 2.0 USES

The Smart Vent® units are engineered mechanically operated flood vents (FVs) employed to equalize hydrostatic pressure on walls of enclosures subject to rising or falling flood waters. Certain models also allow natural ventilation.

#### 3.0 DESCRIPTION

### 3.1 General:

When subjected to rising water, the Smart Vent<sup>5</sup> FVs internal floats are activated, then pivot open to allow flow in either direction to equalize water level and hydrostatic pressure from one side of the foundation to the other. The FV pivoting door is normally held in the closed position by a buoyant release device. When subjected to rising water, the buoyant release device causes the unit to unlatch, allowing the door to rotate out of the way and allow flow. The water level stabilizes, equalizing the lateral forces.

Each unit is fabricated from stainless steel. Smart Vent<sup>®</sup> Automatic Foundation Flood Vents are available in various models and sizes as described in Table 1. The SmartVENT<sup>®</sup> Stacking Model #1540-511 and FloodVENT<sup>®</sup> Stacking Model #1540-521 units each contain two vertically arranged openings per unit.

#### 3.2 Engineered Opening:

The FVs comply with the design principle noted in Section 2.7.2.2 and Section 2.7.3 of ASCE/SEI 24-14 [Section 2.6.2.2 of ASCE/SEI 24-05 (2012, 2009, 2006 IBC and IRC)] for a maximum rate of rise and fall of 5.0 feet per hour (0.423 mm/s). In order to comply with the engineered opening requirement of ASCE/SEI 24, Smart Vent FVs must be installed in accordance with Section 4.0.

#### 3.3 Ventilation:

The SmartVENT® Model #1540-510 and SmartVENT® Overhead Door Model #1540-514 both have screen covers with ¹/₄-inch-by-¹/₄-inch (6.35 by 6.35 mm) openings, yielding 51 square inches (32 903 mm²) of net free area to supply natural ventilation. The SmartVENT® Stacking Model #1540-511 consists of two Model #1540-510 units in one assembly, and provides 102 square inches (65 806 mm²) of net free area to supply natural ventilation. Other FVs recognized in this report do not offer natural ventilation.

## 3.4 Flood Vent Sealing Kit:

The Flood Vent Sealing Kit Model #1540-526 is used with SmartVENT<sup>5</sup> Model #1540-520. It is a Homasote 440 Sound Barrier<sup>5</sup> (ESR-1374) insert with 21 – 2-inch-by-2-inch (51 mm x 51 mm) squares cut in it. See Figure 4.

#### 4.0 DESIGN AND INSTALLATION

## 4.1 SmartVENT® and FloodVENT®:

SmartVENT® and FloodVENT® are designed to be installed into walls or overhead doors of existing or new construction from the exterior side. Installation of the vents must be in accordance with the manufacturer's instructions, the applicable code and this report. Installation clips allow mounting in masonry and concrete walls of any thickness. In order to comply with the engineered opening design principle noted in Section 2.7.2.2 and 2.7.3 of ASCE/SEI 24-14 [Section 2.6.2.2 of ASCE/SEI 24-05 (2012, 2009, 2006 [BC and IRC)], the Smart Vent® FVs must be installed as follows:

- With a minimum of two openings on different sides of each enclosed area.
- With a minimum of one FV for every 200 square



feet (18.6 m²) of enclosed area, except that the SmartVENT<sup>©</sup> Stacking Model #1540-511 and FloodVENT<sup>©</sup> Stacking Model #1540-521 must be installed with a minimum of one FV for every 400 square feet (37.2 m²) of enclosed area.

#### Below the base flood elevation

W. With the bottom of the FV located a maximum of 12 inches (305.4 mm) above the higher of the final grade or floor and finished exterior grade immediately under each opening.

#### 4:2 Flood Vent Sealing Kit

The Flood Vent Sealing Kit Model 1540-526 is used in conjunction with FloodVENT® Model #1540-520. When installed and tested in accordance with ASTM E283, the FV and Flood Vent Sealing Kit assembly have an air leakage rate of less than 0.2 cubic feet per minute per lineal foot (18.56 l/min per lineal meter) at a pressure differential of 1 pound per square foot (50 Pa) based on 12.58 lineal feet (3.8 lineal meters) contained by the Flood Vent Sealing Kit.

### 5.0 CONDITIONS OF USE 10

The Smart Vent<sup>®</sup> FVs described in this report comply with, or are suitable alternatives to what is specified in those codes listed in Section 1.0 of this report, subject to the following conditions:

8.1 The Smart Vent® FVs must be installed in accordance with this report, the applicable code and the manufacturer's installation instructions in the event of a conflict, the instructions in this report govern.

5.2 The Smart Vent<sup>6</sup> FVs must not be used in the place of "breakaway walls" in coastal high hazard areas, but are permitted for use in conjunction with breakaway walls in other areas.

#### 6.0 EVIDENCE SUBMITTED

- 6.1 Data in accordance with the ICC-ES Acceptance Criteria for Mechanically Operated Flood Vents (AC364), dated August 2015 (editorially revised October 2017).
- 6.2 Test report on air infiltration in accordance with ASTM E283.

#### 7.0 IDENTIFICATION

- 7.1 The Smart VENT<sup>6</sup> models and the Flood Vent Sealing Kit recognized in this report must be identified by a label bearing the manufacturer's name (Smartvent Products, Inc.), the model number, and the evaluation report number (ESR-2074).
- 7.2 The report holder's contact information is the following:

SMART VENT PRODUCTS, INC. 430 ANDBRO DRIVE, UNIT 1 PITMAN, NEW JERSEY 08071 (877) 441-8368

www.smartvent.com info@smartvent.com

TABLE 1--MODEL SIZES

MODEL NAME	MODEL NUMBER	MODEL SIZE (in.)	COVERAGE (sq. ft.)
FloodVENT	1540-520	15 1/4" X 7 1/4"	200
SmartVENT <sup>®</sup>	1540-510	15 <sup>3</sup> / <sub>4</sub> " X 7 <sup>3</sup> / <sub>4</sub> "	200
FloodVENT® Overhead Door	1540-524	15 <sup>3</sup> / <sub>4</sub> " X 7 <sup>3</sup> / <sub>4</sub> "	200
SmartVENT® Overhead Door	1540-514	15 <sup>3</sup> / <sub>4</sub> " X 7 <sup>3</sup> / <sub>4</sub> "	200
Wood Wall FloodVENT®	1540-570	14" X 8 <sup>3</sup> / <sub>4</sub> "	200
Wood Wall FloodVENT® Overhead Door	1540-574	14" X 8 <sup>3</sup> / <sub>4</sub> " ·	200
SmartVENT <sup>©</sup> Stacker	1540-511	16" X 16"	400
FloodVent® Stacker	1540-521	16" X 16"	400

For St: 1 inch = 25.4 mm: 1 square foot = m2




FIGURE 1-SMART VENT: MODEL 1540-510