U.S. DEPARTMENT OF HOMELAND SECURITY FEDERAL EMERGENCY MANAGEMENT AGENCY National Flood Insurance Program

ELEVATION CERTIFICATE

IMPORTANT: Follow the instructions on pages 1–9.

OMB No. 1660-0008 Expiration Date: July 31, 2015

-								1.5	SAL STATE PARTY AND A	DONG PROGRAMME BUSINESS PRINTED	SWALLDACKEN BANGGOOD
				ION A	- PROPER	TY INFORMA	TION	1.33	2020年7月至15年15年15日	ANCE COMP	科学生的特殊的基础工程2000年度。工作2000年
	Building Owner's Nar		7					Policy, Number, Company, NAIC, Number			
A2.	A2. Building Street Address (including Apt., Unit, Suite, and 210 84th Street										100
	City Stone Harbo		State NJ				P Code 08	3247			
	Property Description Block: 83.03 Lot	s: 71.02, 72.02	2, 73.02, 74.02,	79.01	····						
A5.	Building Use (e.g., Re Latitude/Longitude:	Lat. 39° 03' 40'	1	Long	. 74° 45' C	7"		orizontal D	atum: 🗷 N	NAD 1927	□ NAD 1983
A6. A7.	Attach at least 2 photographs of the building if the Certificate is being used to obtain flood insurance.										
A8.	For a building with a crawlspace or enclosure(s): A9. For a building with an attached garage:										
	a) Square footage of crawlspace or enclosure(s) 1070 sq ft a) Square footage of attached garage sq ft										and the second s
	b) No. of permanent flood openings in the crawlspace or enclosure(s) within 1.0 foot above adjacent grade b) Number of permanent flood openings in the attached go within 1.0 foot above adjacent grade									ttached garage	
	c) Total net area of f	lood openings in	A8.b	See	back sq				openings ir		sq in
	d) Engineered flood	openings?	Yes No			d) E	ngineered	flood oper	ilngs?	Yes 🗀	No
			TION B - FLOO	D INSU			M) INFO	RMATION	1		
B1.	NFIP Community Nam Borough of Stone	e & Community N Harbor 345323	lumber 3		B2. County Cape Ma					B3. State New Je	
B4.	Map/Panel Number	B5. Suffix	B6. FIRM Index	Date		anel Effective/	B3. Floo	d Zone(s)	1		ation(s) (Zone
	345323 0001	С	07/15/199	2		15/1992		47	A0,1	use base flo 10'	ou depui)
B10	. Indicate the source o						m B9:	***************************************			
D4.4	☐ FIS Profile ☑ FI		unity Determined	-	her/Source:	NAVD 1988	Ci Othou	/Course:		***************************************	and the second s
	. Indicate elevation dat . Is the building located			NGVD		-				 ⊠ No	
DIZ	Designation Date:				□ OPA	- Chile (Wide 1 100	colour Alcu	(Ol A):		23 110	
			N C – BUILDIN		ATION INE	OPMATION (CHOVEV	DEVIIDE	:0)		
										Construction	
C1.	Building elevations ar *A new Elevation Cert	e based on: tificate will be red	Construction quired when const	Drawing ruction o	f the buildin	Building Under C g is complete.	onstruction	1* [2	y rinisnea (Construction	
C2.	Flevations - Zones At	I-A30. AE. AH. A	(with BFE), VE, V1	-V30. V	(with BFE), A	R, AR/A, AR/AE	, AR/A1-A3	0, AR/AH,	AR/AO. Co	mplete Item	IS
	Elevations – Zones A1–A30, AE, AH, A (with BFE), VE, V1–V30, V (with BFE), AR, AR/A, AR/AE, AR/A1–A30, AR/AH, AR/AO. Complete Items C2.a–h below according to the building diagram specified in Item A7. In Puerto Rico only, enter meters.										
	Benchmark Utilized: Vertical Datum: 1929 Indicate elevation datum used for the elevations in items a) through h) below. NGVD 1929 [] NAVD 1988 [] Other/Source:								-		
	Indicate elevation dat Datum used for buildi	um used for the one of	elevations in items ist be the same as	s a) thro	ugn n) below ed for the Bl	. XINGVU 192 FE.					
	a) Top of bottom floor					6 8	Chec	ok the mea	surement u		
	b) Top of the next high		nent, crawispace,	OI GIICIO	suic noor,	11 , 9		⊠ feet	meters		
			ıctural member (V	Zones o	nly)	N/A			meters		
	 c) Bottom of the lowest horizontal structural member d) Attached garage (top of slab) 					N/A	-	☐ feet	meters		
	e) Lowest elevation of	f machinery or ed	quipment servicing	the bui	ding	11.1		⊠ feet	meters	3	
	(Describe type of equipment and location in Comments)										
	 f) Lowest adjacent (finished) grade next to building (L/g) g) Highest adjacent (finished) grade next to building (H/g) 					6 2	3 7 7	feet ⊠ feet	meters		
	h) Lowest adjacent g				ncluding	6.4	1	⊠ feet	meters		
	structural support										
	:	SECTI	ON D - SURVE	YOR, E	NGINEER,	OR ARCHITE	CT CERTI	FICATIO	V		
oform	ertification is to be sig ation. I certify that the rstand that any false s	information on t	his Certificate repr	esents n	ly best effort	s to interpret the	e data avail	able.			الاه
	eck here if comments:					ngitude in Section				·v	
	eck here if attachment			licensed	l land survey	or? Yes	⊠ No			LODIA	CE DE
	ier's Name Lee Thomas					License N 23921	lumber	***************************************		SINDPLA SE,	AL .
Title		avor	***************************************	Compar	y Name as*Amey*S	haw, Inc.	7		7	1	RE.
Professional Land Surveyor Address					-	State NJ		Code 202	7	Jord .	12.12
	Dune Drive, Ste. 8	24		Avalor	.47 17	Telephone	100	-04	-11 11	1 6	•

ELEVATION CERTIFICATE, page 2 IMPORTANT: In these spaces, copy the corresponding information from Section A. FOR INSURANCE COMPANY USE Building Street Address (including Apt., Unit, Suite, and/or Bldg. No.) or PO. Route and Box No. Policy Number: 210 84th Street State ZIP Code City Company NAIC Number Stone Harbor NJ 08247 SECTION D - SURVEYOR, ENGINEER, OR ARCHITECT CERTIFICATION (CONTINUED) Copy both sides of this Elevation Certificate for (1) community official, (2) insurance agent/company, and (3) building owner. A8.c. 6 Smartvents 9Model #1540-510) were installed to cover 200 square feet each. See attached. C2.e. HVAC Platform SECTION E - BUILDING ELEVATION INFORMATION (SURVEY NOT REQUIRED) FOR ZONE AO AND ZONE A (WITHOUT BFE) For Zones AO and A (without BFE), complete Items E1--E5. If the Certificate is Intended to support a LOMA or LOMR-F request, complete Sections A, B, and C. For items E1-E4, use natural grade, if available. Check the measurement used. In Puerto Rico only, enter meters. E1, Provide elevation information for the following and check the appropriate boxes to show whether the elevation is above or below the highest adjacent grade (HAG) and the lowest adjacent grade (LAG). a) Top of bottom floor (including basement, crawlspace, or enclosure) is ☐ feet ☐ meters ☐ above or ☐ below the HAG. b) Top of bottom floor (including basement, crawlspace, or enclosure) is ☐ feet ☐ meters ☐ above or ☐ below the LAG. E2. For Building Diagrams 6-9 with permanent flood openings provided in Section A Items 8 and/or 9 (see pages 8-9 of Instructions), the next higher floor (elevation C2.b in the diagrams) of the building is ☐ feet ☐ meters above or below the HAG. E3. Attached garage (top of slab) is ☐ feet ☐ meters ☐ above or ☐ below the HAG. E4. Top of platform of machinery and/or equipment servicing the building is ☐ feet ☐ meters above or below the HAG. E5. Zone AO only: If no flood depth number is available, is the top of the bottom floor elevated in accordance with the community's floodplain management ordinance? TYes □ No □ Unknown. The local official must certify this information in Section G. SECTION F - PROPERTY OWNER (OR OWNER'S REPRESENTATIVE) CERTIFICATION The property owner or owner's authorized representative who completes Sections A. B., and E for Zone A (without a FEMA-issued or community-issued BFE) or Zone AO must sign here. The statements in Sections A, B, and E are correct to the best of my knowledge. Property Owner or Owner's Authorized Representative's Name City State ZIP Code Address Telephone Date Signature Comments ☐ Check here if attachments. SECTION G - COMMUNITY INFORMATION (OPTIONAL) The local official who is authorized by law or ordinance to administer the community's floodplain management ordinance can complete Sections A, B, C (or E), and G of this Elevation Certificate. Complete the applicable item(s) and sign below. Check the measurement used in Items G8-G10. In Puerto Rico only, enter meters. G1. [7] The information in Section C was taken from other documentation that has been signed and sealed by a licensed surveyor, engineer, or architect who is authorized by law to certify elevation information. (Indicate the source and date of the elevation data in the Comments area below.) G2. [7] A community official completed Section E for a building located in Zone A (without a FEMA-issued or community-issued BFE) or Zone AO. G3. The following information (Items G4-G9) is provided for community floodplain management purposes. G5. Date Permit Issued G6. Date Certificate Of Compliance/Occupancy Issued G4. Permit Number ☐ Substantial Improvement G7. This permit has been issued for: New Construction G8. Elevation of as-built lowest floor (including basement) of the building: feet meters Datum ☐ meters G9. BFE or (in Zone AO) depth of flooding at the building site: ☐ faet feet meters G10.Community's design flood elevation: Datum Title Local Official's Name Telephone Community Name

Date

Replaces all previous editions.

Signature Comments

Building PhotographsSee Instructions for Item A6

		For Insurance Company Use:
Building Street Addre	ss (including Apt., Unit, Suite, and/or Bidg. No.) or P.O. Route and Box	Policy Number
210 84 th Street		
City	State ZIP Code	
Stone Harbor	NJ 08247	

If using the Elevation Certificate to obtain NFIP flood insurance, affix at least two building photographs below according to the instructions for Item A6. Identify all photographs with: date taken; "Front View" and "Rear View"; and if required, "Right Side View" and "Left Side View". If submitting more photographs than will fit on this page, use the Continuation Page, following.



DATE: June 12, 2013, Front View of Residence



DATE: June 12, 2013, Rear View of Residence



ICC-ES Evaluation Report

ESR-2074

Reissued February 1, 2011

This report is subject to renewal in two years.

www.icc-es.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

DIVISION: 08 00 00—OPENINGS Section: 08 95 00—Vents

REPORT HOLDER:

SMART VENT®, INC.
450 ANDBRO DRIVE, SUITE 2B
PITMAN, NEW JERSEY 08071
(856) 307-1468
www.smartvent.com
eval@smartvent.com

EVALUATION SUBJECT:

SMART VENT® AUTOMATIC FOUNDATION FLOOD VENTS:
FLOODVENT™ MODEL #1540-520; FLOODVENT™
STACKING MODEL #1540-521; SMARTVENT™ MODEL
#1540-510; SMARTVENT™ STACKING MODEL #1540-511;
WOOD WALL FLOOD MODEL #1540-570; WOOD WALL
FLOOD OVERHEAD DOOR MODEL #1540-574;
FLOODVENT™ OVERHEAD DOOR MODEL #1540-524;
SMARTVENT™ OVERHEAD DOOR MODEL #1540-514

1.0 EVALUATION SCOPE

Compliance with the following codes:

- 2006 International Building Code® (IBC)
- 2006 International Residential Code® (IRC)

Properties evaluated:

- Physical operation
- Water flow

2.0 USES

The Smart Vent® units are automatic foundation flood vents (AFFVs) employed to equalize hydrostatic pressure on nonfire-resistance-rated foundation walls, rolling-type overhead doors and building walls subject to rising or falling flood waters. Certain models also allow natural ventilation in accordance with Section 1203 of the IBC or Section 408.1 of the IRC.

3.0 DESCRIPTION

3.1 General:

When subjected to pressure from rising water, the Smart Vent® AFFVs disengage, then pivot open to allow flow in either direction to equalize water level and hydrostatic pressure from one side of the foundation to the other. The AFFV pivoting door is normally held in the closed position by a buoyant release device. When subjected to rising water, the buoyant release device causes the unit to

unlatch, allowing the plate to rotate out of the way and allow flow. The water level stabilizes, equalizing the lateral forces. Each unit is fabricated from stainless steel, and each opening provides 76 square inches (49 032 mm²) of net free area for flood mitigation in the open position. The SmartVENT™ Stacking Model #1540-511 and FloodVENT™ Stacking Model #1540-521 units each contain two vertically arranged openings per unit, providing 152 square inches (98 064 mm²) of net free area for flood mitigation in the open position.

3.2 Engineered Opening:

The AFFVs comply with the design principle noted in Section 2.6.2.2 of ASCE/SEI 24 for a maximum rate of rise and fall of 5.0 feet per hour (0.423 mm/s). In order to comply with the engineered opening requirement of ASCE/SEI 24, Smart Vent AFFVs must be installed in accordance with Section 4.0.

3.3 Model Sizes:

The FloodVENT™ Model #1540-520, SmartVENT™ Model #1540-510, FloodVENT™ Overhead Door Model #1540-524, and SmartVENT™ Overhead Door Model #1540-514 units measure 15³/₄ inches wide by 7³/₄ inches high (400 by 196.9 mm). The Wood Wall Flood Model #1540-570 and Wood Wall Flood Overhead Door Model #1540-574 units measure 14 inches wide by 8³/₄ inches high (355.6 by 222.25 mm). The SmartVENT™ Stacking Model #1540-511 and FloodVENT™ Stacking Model #1540-521 units measure 16 inches wide by 16 inches high (406.4 by 406.4 mm).

3.4 Ventilation:

The SmartVENT® Model #1540-510 and SmartVENT® Overhead Door Model #1540-514 both have screen covers with ¹/₄-inch-by-¹/₄-inch (6.35 by 6.35 mm) openings, yielding 51 square inches (32 903 mm²) of net free area to supply natural ventilation. The SmartVENT™ Stacking Model #1540-511 consists of two Model #1540-510 units in one assembly, and provides 102 square inches (65 806 mm²) of net free area to supply natural ventilation. Other AFFVs recognized in this report do not offer natural ventilation.

4.0 INSTALLATION

SmartVENT[®] and FloodVENT[™] are designed to be installed into walls or overhead doors of existing or new construction from the exterior side. Installation of the vents must be in accordance with the manufacturer's instructions, the applicable code and this report. The mounting straps allow mounting in wood, masonry and concrete walls up to 12 inches (305 mm) thick. In order to

comply with the engineered opening design principle noted in Section 2.6.2.2 of ASCE/SEI 24, the Smart Vent® AFFVs must be installed as follows:

- With a minimum of two openings on different sides of each enclosed area.
- With a minimum of one AFFV for every 200 square feet (18.6 m²) of enclosed area, except that the SmartVENT™ Stacking Model #1540-511 and FloodVENT™ Stacking Model #1540-521 must be installed with a minimum of one AFFV for every 400 square feet (37.2 m²) of enclosed area.
- Below the base flood elevation.
- With the bottom of the AFFV located a maximum of 12 inches (305.4 mm) above grade.

5.0 CONDITIONS OF USE

The Smart Vent[®] AFFVs described in this report comply with, or are suitable alternatives to what is specified in, those codes listed in Section 1.0 of this report, subject to the following conditions:

- 5.1 The Smart Vent® AFFVs must be installed in accordance with this report, the applicable code and the manufacturer's installation instructions. In the event of a conflict, the instructions in this report govern.
- 5.2 The Smart Vent® AFFVs must not be used in the place of "breakaway walls" in coastal high hazard areas, but are permitted for use in conjunction with breakaway walls in other areas.

6.0 EVIDENCE SUBMITTED

Data in accordance with the ICC-ES Acceptance Criteria for Autematic Foundation Flood Vents (AC364), dated October 2007.

7.0 IDENTIFICATION

The Smart VENT[®], models recognized in this report must be identified by a label bearing the manufacturer's name (Smart Vent, Inc.), the model number, and the evaluation report number (ESR-2074).